

Power PRO series

PJ1

With built-in PICO projector

14.1 MP | 7X Zoom | 3.0" LCD

Available Colors: ●



More power, More full

If you want it, You want it all! Including the ability to share the big picture and all that comes with it! GE's PJ1 is equipped with the ability to record HD video on the fly and photos, all larger than life. Put your best foot forward with the new GE PJ1 and you're images will take center stage everytime.



imagination at work

Camera Features

PJ1



PICO projector

Projects your camera images and videos up to 70° diagonally on any surface for easy sharing.



optical image stabilization

Automatically adjusts for unintentional camera movements, giving you clear, crisp pictures every time.



PICO+PC

Projects the images and videos from your PC through the camera's built-in PICO projector.



HD 720p video

Captures all of your videos in high definition 720p resolution.



3200 ISO

Improves pictures in low lighting condition for optimal exposure.



high dynamic range

In-camera feature adjusts exposure for more detail in light and dark scenes.



face auto exposure

Automatically enhances facial features detected by the camera for true subject highlighting.



smile detection

The shutter automatically releases when the subject's smile appears.

SPECIFICATIONS*

PJ1

Effective Image Sensor Pixels	14.1 Megapixels
Image Sensor	14.2 Megapixels [1/2.3" Charge Coupled Device (CCD)]
Lens Focal Length F = [35mm film equivalent]	5.05 mm (Wide) — 35.35 mm (Tele)
F number	[28 mm (Wide) — 196 mm (Tele)]
Lens Construction	f / 3.9 (Wide) — f / 5.8 (Tele)
Optical Zoom	14 elements in 11 groups
Focusing Range	7x Normal: (Wide) 23.6 in. ~ ∞ / 60 cm ~ ∞, (Tele) 47.2 in. ~ ∞ / 120 cm ~ ∞ Macro: (Wide) 2.0 in. ~ 47.2 in. / 5 cm ~ 120 cm, (Tele) 47.2 in. ~ ∞ / 120 cm ~ ∞
Anti-Handshake	Optical Image Stabilization
Digital Zoom	6x Digital Zoom (Combined Zoom: 42x)
Number of Recording Pixels	
Still Image	14MP: 4320×3240, (3:2) 12MP: 4320×2880, (16:9) 10MP: 4320×2432, 8MP: 3264×2448, 5MP: 2592×1944, 3MP: 2048×1536, 2MP: 1920×1080, 0.3MP: 640×480
Movie	1280×720 pixels: 30 fps / 15 fps, 640×480 pixels: 30 fps / 15 fps, 320×240 pixels: 30 fps / 15 fps 1280×720 pixels: 30 fps : continuous up to 29 min.
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	Exif 2.2 (JPEG)
Movie	Movie Format: MOV (MPEG-4 / H .264), Audio: G.711 [Monaural]
Shooting Modes	Auto, Manual, ASCN, Scene (Portrait, Image Stabilization, Sport, Children, Indoor, Leaf, Beach, Text, Party, ID, Fisheye, Panning shot, Photo frame, Pro focus, Snow, Sunset, Fireworks, Glass, Museum, Landscape, Night Landscape, Night Portrait Sketch), Panorama, Movie
Detection Features	Face, Smile, Blink
Red-eye Removal	Yes
High Dynamic Range	Yes
PICO	
Image Size	5 to 70 in.
Throw Distance	Approx. 20cm to 2.5 m
Resolution	640×360
Brightness	Up to 15 lumens (Peak)
Contrast ratio	300:1
PICO Connect	PC Link
LCD Display	3.0 inch (230,400 pixels) Auto Adjust Brightness LCD
ISO Sensitivity	Auto, ISO 80 / 100 / 200 / 400 / 800 / 1600 / 3200
AF Method	Single AF, Multi-AF (TTL 9-point), Face-Detection + Face AE, AF Assist Light (On / Off)
Exposure Metering Method	Artificial Intelligence AE (Ai AE), Center-weighted Average, Spot (Fixed to center of frame)
Exposure Control Method	Program AE (AE-lock available)
Exposure Compensation	± 2 EV in 1/3 Step increments
Shutter Speed	4 ~ 1/2000 seconds (Manual: 30 seconds)
Continuous Shooting	Approx. 1.39 fps (Large / Fine Mode)
Playback Modes	Single Photo, Index (9 / 16 thumbnails), Slide Show, Date, Movie (Slow-Motion possible) Zoom (Approx. 2x ~ 8x), Audio, Histogram Display
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual
Internal Flash (Shooting Range)	Auto, Red-Eye Reduction, Forced Flash, No Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro Gno. 5.5 (ISO 100) Shooting Range: (Wide) Approx. 19.6 in. ~ 157.5 in. / Approx. 0.5 m ~ 2.8 m (ISO 400) (Tele) Approx. 31.4 in. ~ 106.3 in. / Approx. 0.8 m ~ 1.8 m (ISO 400)
Recording Media	Internal Memory: Approx. 18 MB SD Card / SDHC Card (Up to 16 GB support)
Other Features	PictBridge, ExifPrint Support, Multi-language Support (26 languages)
Jacks	Micro USB2.0 / AV-OUT (Integrated Proprietary Connector)
Power	Rechargeable Lithium-ion Battery GB-50, 3.7V 950mAh
Shooting Capability (Battery Performance)	Approx. 260 shots (based on CIPA Standards) PICO time: Approx. 70 min
Operation Environment	Temperature: 32° ~ 104° F / 0° ~ 40°C, Humidity: 0 ~ 90%
Dimensions (W x H x D)	3.97 in. x 2.5 in. x 0.8 in. / 100.8 mm x 64.5 mm x 21.2 mm
Mass	Approx. 4.4 oz. / 125g (Body only)
Supplied Accessories	Picture Cradle, Remote Control, Rechargeable Lithium-ion Battery, AC Adapter, Battery Charger, USB Cable, Extension Cable, Wrist Strap, CD-ROM, Manual, Quick Start Guide, Feature Guide, Warranty Card



*Design and specifications are subject to change without notice.
For complete specifications and detailed product information, please visit www.ge.com/digitalcameras.

V 1101